# CD715x

**BRIGHTNESS**
2400 ANSI lumens (boost)
2100 ANSI lumens (standard)
1600 ANSI lumens (eco)
**RESOLUTION**
1024x768 true XGA
1280x1024 SXGA compressed
**DISPLAY TYPE**
TI DMD 0.7”, 12° DDR, DLP chip
**CONTRAST RATIO**
2000:1
**ASPECT RATIO**
4:3 Native
16:9 Compatible
**LAMP**
200 watt OSRAM VIP
**LAMP LIFE**
2000 hours (boost)
3000 hours (standard)
4000 hours (eco)

*Special features of the CD715x include:*

***User friendly lamp replacement****—Top cover access means no need for dismounting the projector to change the lamp.*
***Custom start-up screen****—Download a jpeg file to customize your start-up image.*
***Three lamp modes****—Change your lamp output for varying light conditions and save on lamp life.*
***Multiple inputs****—Connect to multiple peripheral systems at the same time.*
***Color management****—Adjust individual colors as needed.*

**OPTIONAL ACCESSORIES:**
**Extended Warranty**
**Mac Adapter / DVI Adapter**
**Cable: Audio / VGA / Component / Composite Video**
**Universal Ceiling Mount / Suspension Pole/ Round Flush Kit**
**Spare Lamp Module**

**SHIPS WITH:**
**Laser Remote Control**
**User Manual/CD ROM**
**Power Cord, Lens Cap & Soft Carry Case**
**USB Mouse, S-Video Cable**
**DVI/VGA 15 pin Computer Cable**

**DIAGONAL IMAGE SIZE**
37” - 240” inches
**PROJECTION LENS**
Manual zoom/focus
**ZOOM RATIO**
1.22:1
**THROW DISTANCE**
4.9’ - 26’ feet
1.5 - 8 meters
**THROW RATIO**
1.63 - 2.0 (x screen width)
**INPUTS**
Component Video (R,G,B)
Composite Video (R/L audio)
DVI-I
Mini jack audio
S-Video
VGA
**OUTPUTS**
VGA, Mini jack audio
**PROJECTOR COMPATIBILITY**
VGA, SVGA, XGA, SXGA, Mac
**CONTROLS**
RS232, USB mouse control

**KEYSTONE**
+/- 15° vertical
**VIDEO**
NTSC, NTSC 4.43, PAL, SECAM
**HDTV / EDTV / SDTV**
480i/p, 576i/p, 720p, 1080i
**AUDIO**
1 X 2 watt speakers
**DIMENSIONS (WxDxH)**
12.9” x 9.4” x 3.5” inches
32.8 x 23.8 x 8.8 cm
**WEIGHT**
7.8 lbs / 3.55 kg
**DECIBEL RATING**
36 dB / 34dB / 31 dB
**WARRANTY**
3 year parts & labor
90 day lamp
**FCC CERTIFICATION**
Class B

**H-SCAN FREQUENCY**
Horizontal—15-90 kHz
**V-REFRESH RATE**
Vertical—50-85 kHz
**POWER SUPPLY**
110-240 Voltage
**PWR. CONSUMPTION**
230 Watts (boost)
200 Watts (standard)
180 Watts (eco)

BOXLIGHT® CORPORATION
**19462 Powder Hill Place, Suite 101**
**Poulsbo, WA 98370**

**www.boxlight.com**
**Direct 800.762.5757**
**International 360.779.7901**
**Partners 866.688.3636**

© 2007 BOXLIGHT Corporation. All rights reserved. Specifications are subject to change without notice. 6.1.07